

# 1.8 TFT 128x160 LCD 1.77 TFT LCD SPI



## PRODUCT INFORMATION

TFT LCD DISPLAY

<b>اسم LCD</b>	1.8 بوصة شاشة TFT 128x160 وحدة شاشة LCD 1.77 بوصة وحدة TFT LCD مع واجهة SPI		
<b>نوع</b>	وحدة LCD بوصة 1.8 (TFT)*1.77	<b>الدقة</b>	بيكسل 128 (RGB) X160
<b>IC سائق</b>	ST7735S	<b>نسبة التباين</b>	300: 1
<b>البعد المخطط</b>	ملم 34.70 × 46.70 × 2.50	<b>منطقة نشطة (HxV)</b>	ملم 28.03x35.04
<b>عرض الاتجاه</b>	00:00	<b>واجهه المستخدم</b>	ديوس 22 ، SPI بت 8
<b>الإضاءة الخلفية</b>	ليد 2	<b>سطوع</b>	م 230cd / 2
<b>درجة حرارة التشغيل</b>	-20 °C ~ 70 °C	<b>التيار / الجهد لإمداد الإضاءة الخلفية</b>	ملي أمبير ، 3.3 فولت 10

\* عبارة عن شاشة عرض بلورية سائلة ذات مصفوفة نشطة ملونة صغيرة الحجم V.1 KWH018TW12-F03 (LCD)

\* إضاءة خلفية ، FPC ، IC مشغل ، TFT LCD يتكون من لوحة.

\* بدقة TFT LCD 160 × 128 إنها وحدة.

\* تتوفر إضاءة خلفية بخيارات سطوع مختلفة من 200 إلى 1500 شمعة / متر مربع.

\* يمكن تصميم لوحة اللمس المحددة وتخصيصها.

\* متوافق مع RoHS & REACH.

\* إذا لم تتمكن من العثور على واحد مناسب ، فاتصل بنا للحصول على توصية.

# PRODUCT DISPLAY

TFT LCD DISPLAY



TFT LCD DISPLAY

## PRODUCT DETAILS



- High Brightness reaches to 230 cd/m<sup>2</sup>
- 20 Pin soldering FPC 8-bit SPI interface
- 1.8 Inch 128x160 TFT LCD display module
- 2 White LED in parallel & With ST7735S
- Focus on production and quality assurance
- Support OEM / ODM service

# APPLICATION

TFT LCD DISPLAY



01 Civilian equipment



02 Office tools



03 Traffic instrument



04 Mini screen



05 Medical and beauty equipment



06 Smart device



07 Automation



08 Control system